

4G LTE Video Intercom

No wiring needed, No Wi-Fi issues



- 4G LTE
- H.265
- HD 1080
- Remote Door Open

The 4G AN1912 is a digital video intercom (Multi-Resident), Operates on a 4G network or wired network, can be configured and managed by the mobile APP.

Features;

- 4G IP videophone
- Instant videocall to mobile app
- 24/7 video recording
- Face detection alarm
- Max. 1000 room numbers.
- Max. 1000 MI fare cards (optional)
- Max. 1000 PIN codes
- 4G LTE/3G/GSM network
- 1080P H.265 video
- 2-way audio
- SD card storage up to 128GB

AN1912 Multi-Tenant 4G Video Intercom

Intercom Features:

- ◆ 4G VoIP videocall / 3G mobile voice call
- ◆ AI face detection
- ◆ Support 3000 users
- ◆ Support 1000 RFID 13.56MHz Mifare cards
- ◆ Support 1000 PIN codes
- ◆ 24/7 recording/monitoring
- ◆ 4G LTE/3G/GSM networks
- ◆ HD video surveillance
- ◆ SD card storage up to 128GB
- ◆ Hidden antenna

APP Features:

- Add/delete/modify flat number/phone number/ PINcode/ Mifare card.
- Unlock the door remotely
- Manage multiple devices
- Play video record
- Check call/access log
- Door unlock/lock and offline notifications
- Take screenshot



Applications:

Multi-Tenant 4G video intercom that can be used for apartment buildings, gated communities, residential complex, assisted care centers.

It offers building owners and property managers alike the most versatile, feature-rich intercoms for multi-tenant properties. With our advanced technology, tenants or grounds guards can easily identify entrants before granting them access into the building.



AN1912 Multi-Tenant 4G Video Intercom

Specifications:

Model Number		AN1912
Video	Image Sensor	1/2.7" 2MP CMOS
	Image Compression	H.265
	Image Frame Rate	25fps maximum
	Resolution	1080P (1920 x 1080), VGA (720 x 576)
	Lens	2.8 mm
	View angle	H:90° V:80°
	Day Vision	Color Image, auto switch IR-CUT
	Nigh Vision	BW Image, 6 Infrared LED
Audio	Audio Input	Omnidirectional Mic
	Audio Output	Built-in Speaker
	Bidirectional Talk	Dual-way bidirectional talk
	Audio Compression	AMR
Display	LED digital display	5-Digit
Storage	SD Card	Micro SD,128GB (Max)
Network	Ethernet	10/100Mbps (PoE optional)
	Mobile network	4G LTE/3G WCDMA/2G GSM
Call	Video Call	Android and iOS APP
	Voice Call	Mobile voice call
Door Release	Unlock door	Remotely by APP, mobile voice call DTMF, PIN code, Mifare card
	Relay Outputs	2
	Exit Button input	1
	Detector input	1
	Relay type	NO & NC
	Relay time	3,8,15,30,60,300,600 seconds
	Relay load	10A(AC240V/DC24V)
Operation Mode	Keypad	Mechanical Button
	Reader	Type A Mifare 13.56 MHz Card reader
Alarm	Face detection	Record 10s video clip
	Notification	Alarm , Warning
Power	Power Supply	12V-24V DC 1.5A
	Power Consumption	10 Watts (Max.)
Environment	Operating Temperature	-10 to +50 °C (+14 to +124 °F)
	Operating Humidity	10~80%RH
	Storage Temperature	-20°C ~ 60° (-4°F ~ 140°F)
	Storage Humidity	0% ~ 90%
General	Reset	Hardware reset button
	SIM Card	Micro SIM card
	Material	Alum-Alloy + Acrylic
	IP Rating	IP65
	Product Dimension	276(L)*116(W)*50(H) mm
	Net Weight	2.5Kg