

Big Button IP Phone

Aristel



AN R15PVM Health Care Phone

A high-quality, cost effective IP solution for aged and health care facilities.

- Easy to use with big buttons
- HD Voice with Volume & Tone Controls
- 3 Memory Buttons
- Hearing Aid Compatible (HAC)
- Simple One Touch Message Retrieval Button
- Redial Button
- Loudspeaker / Hands-free
- Call Log / Missed Calls
- Large Message Waiting Indicator.
- Supports PoE
- Tamper-proof Setting
- Fully Compatible with Asterisk, BroadSoft Platform
- Australian Tones & Compliance

Distributed by:
Aristel Networks Pty Ltd
1/25 Howleys Road,
Notting Hill, Victoria, 3168, Australia
T: 03 8542 2300 Freecall: 1800 00 21 33 F: 03
9544 3299 e:sales@aristel.com.au -
www.aristel.com.au

AN R15PVM Big Button IP Phone

Phone Features

- 1 Line (Support 1 SIP account)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable
- Speed Dial, Hotline
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries)
- 5 Remote Phone Book URL Supported
- LDAP Phone Book
- Multi-Language Support
- Compatible with all leading IP PBX Systems

IP-PBX Features

- MWI
- Music on hold, Intercom
- Call Pickup, Group Call Pickup
- Call Recording
- Anonymous Call, Anonymous Call Rejection

Audio Features

- HD Voice with high volume
- Hearing Aid Compatible (HAC)
- Wideband Codec: G.722
- Narrowband Codec: PCMA, PCMU, G.729, G723_53, G723_63, G726_16, G726_24, G726_32, G726_40
- VAD, CNG, Echo Cancellor
- Full-Duplex Speakerphone

Security Features

- Supports HTTPS (SSL)
- Supports SRTP for Voice Data Encryption
- Supports Login for Administration
- SIP Over TLS

Network Features

- SIP V1(RFC2543), V2(RFC3261)
- Static IP/DHCP for IP configuration
- 3 DTMF modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- NTP for Auto Time Setting
- TFTP/FTP/HTTP/HTTPS Protocols
- 802.1Q VLAN

Administration Features

- Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Management with Web interface, Keypad on the phone and auto provisioning
- SNMP
- TR069

Physical Features

- Audiocodes Chipset
- 2.9" 132x64 Graphical LCD with Backlight
- 25 Keys (with 1 Message key, 4 Soft Keys, 3 Image Programmable Keys)
- 3 LED Lights (1 Power Light, 1 Handsfree Light and 1 SOS Light)
- RJ9 Handset Jack and Headset Jack
- 2 RJ45 10/100 Ethernet Jacks
- AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- PoE: IEEE 802.3af
- Box Size: 248 x 204 x 107 (mm), weight: 1.19 kg

