



Smart Security IP Intercom - IS710v2




The ESCENE IP Intercom - IS710 (V2), has been developed to customers' needs. Its classic fascia design is waterproof, dustproof and vandal resistant. It is ideal for many applications where SIP connectivity is required.

Product Features

- One button calling with full-duplex voice intercom.
- Fascia is 5mm thick drawn aluminum for strength and durability.
- Supports POE and local 12v power supply.
- Flush mount or surface mount with the surface mount cabinet supplied as standard.
- Two relays for releasing 2 doors or activating 2 devices.
- Gasket seals provide waterproof and dustproof level to IP65.
- Two input sensors for monitoring or egress button use.

Technical Information

Intercom features
<ul style="list-style-type: none">• WEB support Multi-Language• 1 SIP account• Hotline, Call forward, DND, Auto-answer, Volume control• Default Ring tone selection/import/delete, Custom Warning Ring tone selection/import/delete• Time setting (SNTP/SIP Server/Manual)• Support SIP main/standby server
Network parameters
<ul style="list-style-type: none">• SIP v1 (RFC2543), v2 (RFC3261), DNS SRV (RFC3263)• NAT Traversal: STUN mode.• DTMF: In-Band, RFC2833, SIP Info, Auto• HTTP/HTTPS Web Management• IP Assignment: Static/DHCP/PPPoE• Network support Bridge mode; TFTP/DHCP/PPPoE
Security
<ul style="list-style-type: none">• LLDP, VLAN QoS (802.1pq), VPN(L2TP)• Transport Layer Security (TLS)• Digest authentication using MD5/MD5-sess. secure configuration file via AES encryption; Phone lock for personal privacy protection; Admin/User 2-level configuration mode.
Voice features
<ul style="list-style-type: none">• Wideband Codec: G.722• Narrowband codec: G.711μ/A, G.723.1;G.726, G.729a/b, iLBC; VAD, CNG, AEC,
Physical properties
<ul style="list-style-type: none">• 1 hotline programmable key (Speed dial, Intercom etc.); 1 light touch button• 1xRJ45 10/100M Ethernet ports; PoE, IEEE 802.3af, class 0.• Power adapter: AC 100~240V input DC 12V/1A output;• Net weight: 0.52KG, Gross weight: 0.65KG. Each motherboard port, check the picture illustration below "Mother Board Interface".
Carton packaging
The whole Size : 162*112*40mm
Product Certification

Platform Compatibility Test (non-certificate)
ZTE/Alcatel-Lucent/Asterisk/Broadsoft/Metaswitch/Yeastar/Avaya/3CX/Elastix/HUAWEI etc.



Distributed by:

Aristel Networks Pty Ltd
1/25 Howleys Rd Notting Hill Vic 3168
P: 03 8542 2300 F: 03 9544 3299
Freecall: 1800 002 133
www.aristel.com.au